

MAXBOND PU PRIMER

POLYURETHANE PRIMER

About The Product

Maxbond PU Primer is a polyurethane primer containing polyurethane prepolymer and quick drying solvents. It is used in substrate preparation to counter the effects of substrate humidity and porosity, to improve application rate of polyurethane coatings and enhance bonding of polyurethane sealants. For use over concrete, masonry and metal surfaces.

Design Features

- High penetrating ability
- Quick drying
- Excellent bond

Limitations

- Do not apply over damp surfaces
- Do not apply over plastic foams or solvent sensitive surfaces.

Product Characteristics

Color	Yellowish transparent liquid
Specific Gravity	0.95 ±0.05
Volume Solids	>40%
Flash Point	>25°C / 77°F
Drying Time @ 25°C, 80% RH	2-3 hours

Surface Preparation

All surfaces must be clean, dry and free from oils, wax and other contaminants. Metal shall be wire brushed and free of rust, paint and other coating.

The Installation

Stir Maxbond PU Primer well before use. Apply by brush, roller or spray at a rate of 0.2 liter per m² depending on porosity of the substrate. Use only in well ventilated area and keep away from open flame. Let the primer penetrate the substrate and protect from air borne dust.

Packaging

16 kg pail

MAXBOND PU PRIMER

POLYURETHANE PRIMER

Coverage

Approximately 0.2 - 0.3 kg per m² on smooth surface

Storage

Store in sealed original packaging in well ventilated, cool and dry space away from sunlight and heat source.

Shelf Life

12 months

Health & Safety

This product contains solvent and is flammable. Do not use near open flame or in enclosed space without ventilator or breathing apparatus. Wear protective gloves and safety goggles when handling and avoid excessive inhalation. Upon contact with skin, wash with soap and water. In case of eye contact, flush with water and seek medical attention immediately.

Note The information in this publication is given in good faith and is based on our current knowledge and experience.

We assume no liability, expressed or implied, to any particular use and/or application.

All information herein is effective from the date of issue and supersedes all previous editions.

* Values are typical and not meant as performance benchmark.